

ADI[®]

HELIOS X Series

Key Features

- High-efficiency amplifiers for powerful, distortion-free sound
- Advanced digital signal processing for customized audio
- Premium drivers for exceptional clarity and bass response
- Durable, rugged enclosures for reliable performance



HELIOS X215



HELIOS X18 SUB



HELIOS X12

HELIOS X15

PRODUCT SPECIFICATION

	X12	X15	X215	X18-Sub
Enclosure:	Sand Blasted Plywood Material			
Configuration Type:	2 – Way active filter			
HF:	1" throat, 2" Voice Coil		1.4 throat, 2" Voice Coil	
LF:	12" Woofer , 3" Voice Coil	15" Woofer , 3" Voice Coil	15" x 2 Woofer, 3" Voice Coil	18" Sub, 4" Voice Coil
Amplifier:	Class D-Bi AMP			Class D
Frequency Range(-10dB):	50Hz-20Khz	45Hz-20Khz	45Hz-20Khz	80Hz-150Hz Low-pass filter select switch
DSP:	With DSP processor and 5 modes can be selected			
Mic Input:	XLR / 1/4" TRS			
Line Input:	¼ TRS / RCA			XLR
Line Output:	XLR			XLR
Max SPL:	124dB / 136dB Max	125dB / 137B Max	128dB / 138B Max	132dB/137dB
RMS Power:	1200 Watts RMS	1500 Watts RMS	1800 Watts RMS	1800 Watts
Max Power:	2400 Watts Peak	3000 Watts Peak	3600 Watts Peak	3600 Watts Peak
Power Voltage:	AC100 V – AC240V			
Dimension:	360x370x620mm	432x445x710mm	430x470x1156mm	690x580x538mm
Weight:	23 (kg)	28 (kg)	44 (kg)	40 (kg)